

MOUNTED REVERSIBLE MOULDBOARD PLOUGH



Model	Number of Furrows	Clearance (cm)	Distance Between Furrows (cm)	Working Width (cm)	Working Depth (cm)	Weight (kg)	Required Power (Hp)
AG-RMP 12-2	2	75	80	25-30-35	26	700	55-60
AG-RMP 12-3	3	75	80	25-30-35	26	840	60-70
AG-RMP 12-4	4	75	80	25-30-35	26	1115	80-90
AG-RMP 12-5	5	75	80	25-30-35	26	1320	90-110
AG-RMP 14-2	2	75	80	30-35-40	28	704	60-65
AG-RMP 14-3	3	75	80	30-35-40	28	911	65-70
AG-RMP 14-4	4	75	80	30-35-40	28	1145	85-90
AG-RMP 14-5	5	75	80	30-35-40	28	1400	90-110
AG-RMP 16-2	2	75	85	35-40-45	30	710	80-85
AG-RMP 16-3	3	75	85	35-40-45	30	918	80-85
AG-RMP 16-4	4	75	85	35-40-45	30	1170	85-90
AG-RMP 16-5	5	75	85	35-40-45	30	1420	100-120
AG-RMP 18-2	2	75	85	40-45-50	32	716	80-90
AG-RMP 18-3	3	75	85	40-45-50	32	925	80-90
AG-RMP 18-4	4	75	85	40-45-50	32	1185	90-110
AG-RMP 18-5	5	75	85	40-45-50	32	1500	120-130

Time savings and reduced fuel consumption. Ease and speed of set-up into the work/transport position. Ease and simple adjustments for the best tractor adaptations. Box section top quality steel frame construction.