



MOUNTED REVERSIBLE HYDRAULIC MOULDBOARD PLOUGH WITH SAFETY PIN



For optimum use of engine power, tractor inter-tire distance adjustment (OPTIONAL). Equipped with bolt safety system. Three positions infinitely variable hydraulic working width adjustment from tractor seat.

Model	Number of Furrows	Clearance (cm)	Distance Between Furrows (cm)	Working Width (cm)	Working Depth (cm)	Weight (kg)	Required Power (Hp)
AG-RMPH 08-2	2	70	75	25-30-35	20	577	45-50
AG-RMPH 08-3	3	70	75	25-30-35	20	740	50-55
AG-RMPH 08-4	4	70	75	25-30-35	20	920	70-80
AG-RMPH 08-5	5	70	75	25-30-35	20	1010	80-90
AG-RMPH 09-2	2	70	75	30-35-40	22	583	45-50
AG-RMPH 09-3	3	70	75	30-35-40	22	745	50-55
AG-RMPH 09-4	4	70	75	30-35-40	22	960	70-80
AG-RMPH 09-5	5	70	75	30-35-40	22	1040	80-90
AG-RMPH 10-2	2	70	75	35-40-45	24	589	50-55
AG-RMPH 10-3	3	70	75	35-40-45	24	750	55-60
AG-RMPH 10-4	4	70	75	35-40-45	24	1000	80-85
AG-RMPH 10-5	5	70	75	35-40-45	24	1100	90-100
AG-RMPH 12-2	2	70	75	40-45-50	26	595	50-55
AG-RMPH 12-3	3	70	75	40-45-50	26	760	60-70
AG-RMPH 12-4	4	70	75	40-45-50	26	1032	80-90
AG-RMPH 12-5	5	70	75	40-45-50	26	1160	90-110