

CONVENTIONAL PLOUGH WITH BOLT SAFETY



Bolt safety ploughs are equipped with bolt safety system preventing any damage on the tractor and on the plough caused by overloading. Easy and quick replacement of the cracked bolt to allow work to continue. High resistible frame construction. Cheapest solution for fields with few obstacles

Model	Clearance (cm)	Distance Between Furrows (cm)	Working Width (cm)	Working Depth (cm)	WEIGHT (KG)					REQUIRED POWER (HP)				
					2 FURROW	3 FURROW	4 FURROW	5 FURROW	6 FURROW	2 FURROW	3 FURROW	4 FURROW	5 FURROW	6 FURROW
AG-PMP 08	60	58	23,5	20	200	258	349	479	585	20-25	30-40	40-50	50-60	65-75
AG-PMP 10	66	67	25,5	24	215	327	502	630	765	30-40	45-50	70-80	80-90	80-90
AG-PMP 12	66	72	30	26	230	350	537	669	780	40-50	55-60	70-85	90-100	95-115
AG-PMP 14	66	76	35	28	240	366	555	702	840	40-50	60-70	80-90	90-110	110-125
AG-PMP 16	66	76	40	30	255	376	561	720	865	50-60	70-80	80-90	100-110	125-135