

MOLDBOARD PLOUGH WITH PIN-CUT



It is manufactured for ploughing fallow grounds. The plough weasily gets rid of all kinds of congestion with its special design and it is prevented from any mechanical damages on the ground by the means of special grooved pin cutting system. The front part of moldboards are manufactured in piece to ensure long life. It doesn't force the tractor, saves time and fuel.

Model	Number of Furrows	Length (mm)	Width (mm)	Height (mm)	Working Depth (mm)	Working Width (Inch)	Space Between Furrows	Weight (kg)	Required Power (Hp)
AG-MMP 12	2	1710	1123	1450	210-300	12-14-16	75	375	50-70
	3	2460	1458	1450	210-300	12-14-16	75	585	60-75
	4	3210	1853	1490	260-330	12-14-16	80	755	75-90
	5	4010	2058	1550	260-330	12-14-16	80	865	90-120
	6	4810	2308	1550	260-330	12-14-16	80	1010	110-130
AG-MMP 14	2	1740	1188	1450	250-350	12-14-16	85	405	60-70
	3	2590	1518	1450	250-350	12-14-16	85	615	75-90
	4	3440	1928	1490	250-350	12-14-16	85	795	90-120
	5	4290	2123	1550	250-350	12-14-16	85	905	110-130
	6	5140	2373	1550	250-350	12-14-16	85	1070	110-130
AG-MMP 16	2	1870	1243	1450	300-450	12-14-16-18	90	425	60-75
	3	2770	1573	1450	300-450	12-14-16-18	90	635	60-90
	4	3670	1988	1490	300-450	12-14-16-18	90	825	90-120
	5	4570	2183	1550	300-450	12-14-16-18	90	935	120-150
	6	5470	2438	1550	300-450	12-14-16-18	90	1095	120-180
AG-MMP 20	2	1970	1343	1450	300-450	12-14-16-18	90-95	465	60-90
	3	2920	1673	1450	300-450	12-14-16-18	90-95	675	60-90
	4	3870	2088	1490	300-450	12-14-16-18	90-95-100	865	90-120
	5	4820	2283	1550	300-450	12-14-16-18	90-95-100	975	120-150
	6	5770	2538	1550	300-450	12-14-16-18	90-95-100	1135	120-180