

MOUNTED FIELD SPRAYER STANDARD BOOM



- The chassis models are produced with high quality material by robotic welding.
- The lock system with pressure spring support the booms opening and closing stably .there is control panel that provides homogeneous and precise spraying.
- Cleanable filter system,3 membrane spraying pump with best performance,
- Fresh water tank independent from main tank.
- Long lasting and cleanable nozzle, the tank washing system, which enables the tank to be washed after sprayin

Specification (unit)	Material of Tank	Capacity of Tank (Lt)	Pump Model (Piston Membrane)	Pump Flow (l/min)	Pump Pressure (Bar)	Control Panel	Work Width (m)	Nozzle Type	Number of Nozzles (number)	Distance Between Nozzles (cm)	Boom Height Adjustment	Boom's Folding Adjustment	Required Tractor Power (HP)	Operating Speed (r/min)	Weight (kg)	Length (cm)	Width (cm)	Height (cm)
DELTA A4	polyethylene	400	C71	71	50	OG 403	10		20	50	Manual	Manual	40	540	145	135	75	135
DELTA A6	polyethylene	600	C71	71	50	OG 403	10	Conical brass nozzle	20	50	Manual	Manual	40	540	156	135	75	150
DELTA A8	polyethylene	800	C71	71	50	OG 403	10		20	50	Manual	Manual	40	540	202	148	75	156
DELTA A10	polyethylene	1000	C71	71	50	OG 403	10		20	50	Manual	Manual	40	540	210	148	75	176