MOUNTED FIELD SPRAYER STANDARD BOOM



reserve the right to make changes and / or improvements in designs & dimensions without notice and without incurring obligation.

The lock system with pressure spring support the booms opening and closing stably .
Long lasting and cleanable nozzle,
3 membrane spraying pump with best performance, there is control panel that provides homogeneous and precise spraying.
Cleanable filter system,
Quick fill up

Specifica (unit		Capacity of Tank (Lt)	Pump Model (Piston Membrane)	Pump Flow (I/ dk)	Pump Pressure (bar)	Control Panel	Work Width (m)	Nozzle Type	Number of Nozzles (number)	Distance Between Nozzles (cm)	Boom Height Ad- justment	Boom's Folding Adjustment	Required Tractor Power (HP)	Operating Speed (r/ min)	Weight (kg)	Length (cm)	Width (cm)	Height (cm)
BETA SP	400 polyethylene	400	C71	71	50	OG 403	10		20	50	Manual	Manual	40	540	145	135	70	135
BETA SP	600 polyethylene	600	C71	71	50	OG 403	10	Conical	20	50	Manual	Manual	40	540	156	135	70	150
BETA SP	800 polyethylene	800	C71	71	50	OG 403	10	brass nozzle	20	50	Manual	Manual	40	540	202	148	85	156
BETA SP :	000 polyethylene	1000	C71	71	50	OG 403	10		20	50	Manual	Manual	40	540	210	148	85	176