

## MOUNTED FIELD SPRAYER HYDRAULIC BOOM



- The chassis models are produced with high quality material by robotic welding.
- The lock system with pressure spring support the booms opening and closing stably .
- The pressure filter to increase spraying efficiency by filtering pressurized water
- Quick fill up
- Clean water tank independent from main tank
- The tank cleaning system that allows the tank to be washed after spraying.
- Cleanable filter system,
- 4 membrane spraying pump with best performance,
- Long lasting and cleanable nozzle,

Specification (unit)	Material of Tank	Capacity of Tank (Lt)	Pump Model (Piston Membrane)	Pump Flow (l/ dk)	Pump Pressure (bar)	Control Panel	Work Width (m)	Nozzle Type	Number of Nozzles (number)	Distance Between Nozzles (cm)	Boom Height Adjustment	Boom's Folding Adjustment	Required Tractor Power (HP)	Operating Speed (r/ min)	Weight (kg)	Length (cm)	Width (cm)	Height (cm)
DELTA B4	polyethylene	400	C96	96	50	OSR 50-3	12	Conical brass nozzle	25	50	Hydraulic	Manual	40	540	226	135	100	217
DELTA B6	polyethylene	600	C96	96	50	OSR 50-3	12		25	50	Hydraulic	Manual	40	540	250	135	100	217
DELTA B8	polyethylene	800	C96	96	50	OSR 50-3	12		25	50	Hydraulic	Manual	40	540	274	148	103	217
DELTA B10	polyethylene	1000	C96	96	50	OSR 50-3	12		25	50	Hydraulic	Manual	40	540	285	148	103	217