



## TRAILED FIELD SPRAYER STANDARD BOOM



- Clean water tank independent from main tank
- Fast filling
- Control that provides homogeneous and precise spraying norm
- Draining system that quickly drains the water remaining in the tank after spraying
- Drawbar that has height adjustment and can be attached to the tractor easily
- Spraying pump with 4 membranes having the best performance
- Filter system with check valve that can be cleaned easily
- Durable wheels that can operate in all kinds of field conditions
- Reflector system that allows the machine to be noticed in traffic
- Durable and cleanable nozzle
- Arm that opens and closes steadily thanks to locking system with pressure spring

Specification (unit)	Material of Tank	Capacity of Tank (Lt)	Pump Model (Piston Membrane)	Pump Flow (l/min)	Pump Pressure (Bar)	Control Panel	Work Width (m)	Nozzle Type	Number of Nozzles (number)	Distance Between Nozzles (cm)	Boom Height Adjustment	Boom's Folding Adjustment	Required Tractor Power (HP)	Operating Speed (r/min)	Weight (kg)	Length (cm)	Width (cm)	Height (cm)
LEPUS SF1000	Polyester	1000	C96	96	50	OPR 40 - 3	12	Conical Brass Nozzle	25	50	Manual	Manual	50	540	410	270	312	137
LEPUS SF1600	Polyester	1600	C96	96	50	OPR 40 - 3	12	conical Brass Nozzle	25	50	Manual	Manual	50	540	446	270	310	144
LEPUS SF2000	Polyester	2000	C96	96	50	OPR 40 - 3	12	Conical Brass Nozzle	25	50	Manual	Manual	50	540	478	270	355	155