

## TRAILED FIELD SPRAYER HYDRAULIC BOOM HIGHT WHEEL



- Spring system that minimizes oscillation on uneven land
- Clean water tank independent from main tank
- Pressure filter that increases spraying efficiency by filtering pressurized water
- Fast filling
- Control that provides homogeneous and precise spraying norm
- Draining system that quickly drains the water remaining in the tank after spraying
- Drawbar that has height adjustment and can be attached to the tractor easily
- Spraying pump with 4 membranes having the best performance
- Filter system that can be cleaned easily and enables fast filling
- Durable wheels that can operate in all kinds of field conditions
- Stop lamps that ensure safety of the machine in traffic
- Lock and spring system that keep the arm stable
- Durable and cleanable nozzle

Specification (unit)	Material of Tank	Capacity of Tank (Lt)	Pump Model (Piston Membrane)	Pump Flow (l/min)	Pump Pressure (Bar)	Control Panel	Work Width (m)	Nozzle Type	Number of Nozzles (number)	Distance Between Nozzles (cm)	Boom Height Adjustment	Boom's Folding Adjustment	Required Tractor Power (HP)	Operating Speed (r/min)	Weight (kg)	Length (cm)	Width (cm)	Height (cm)
LEPUS YHF 1000	Polyester	1000	C96	96	50	OSR 50-5	16	Conical Brass Nozzle	33	50	Hydraulic	Manual	60	540	782	347	272	225
LEPUS YHF 1600	Polyester	1600	C96	96	50	OSR 50-5	16		33	50	Hydraulic	Manual	60	540	820	348	272	225
LEPUS YHF 2000	Polyester	2000	C96	96	50	OSR 50-5	16		33	50	Hydraulic	Manual	60	540	832	385	272	225