

MOUNTED ATOMIZER PULLEY BELT TYPE



- Fast filling
- Control that provides homogeneous and precise spraying norm
- Spraying pump with 4 membranes having the best performance
- Filter system with check valve that can be cleaned easily
- Modular chassis that is produced from high quality material with robotic welding
- Atomizer nozzle with adjustable spray angle and drop stopping feature
- Fan protection wire designed to prevent possible accidents
- Clean water tank independent from main tank
- Tank washing system that allows the tank to be washed after spraying
- Caps that provide direction during operation
- Separator system that allows the fan to be disengaged during operation

SPECIFICATIONS (unit)	Material Of Tank	Capacity of Tank (lt)	Pump Model (Piston Membrane)	Pump Flow (L/Min)	Pump Pressure (Bar)	Control Panel	Nozzle Type	Number of Nozzle (AD)	Fan Diameter (cm)	Working Width (cm)	Required Tractor Power (BG)	Operating Speed (dev/dk)	Air Flow Rate (m ³ /h)	Weight (kg)	Width (cm)	Length (cm)	Height (cm)
DELTA E4	polyethylene	400	C 96	96	50	OSR 50-3	Brass Stopper Turbo	10	75	12,16	50	540	54000	225	150	150	145
DELTA E6	polyethylene	600	C 96	96	50	OSR 50-3	Brass Stopper Turbo	10	75	12,16	50	540	54000	235	150	150	160