

## MOUNTED FIELD SPRAYER HYDRAULIC BOOM



- The spring system minimizing oscillation in rough terrain
- The lock system with pressure spring support the booms opening and closing stably .
- Long lasting and cleanable nozzle,
- The pressure filter to increase spraying efficiency by filtering pressurized water
- Clean water tank independent from main tank
- The hose carrier to ensure the hoses tidy between the control panel and the boom
- 4 membrane spraying pump with best performance,
- there is control panel that provides homogeneous and precise spraying.
- Cleanable filter system,

Specification (unit)	Material of Tank	Capacity of Tank (Lt)	Pump Model (Piston Membrane)	Pump Flow (l/min)	Pump Pressure (Bar)	Control Panel	Work Width (m)	Nozzle Type	Number of Nozzles (number)	Distance Between Nozzles (cm)	Boom Height Adjustment	Boom's Folding Adjustment	Required Tractor Power (HP)	Operating Speed (r/min)	Weight (kg)	Length (cm)	Width (cm)	Height (cm)
BETA HP 600	polyethylene	600	C96	96	50	OSR 50-5	16	Conical brass nozzle	33	50	Hydraulic	Manual	50	540	394	135	103	217
BETA HP 800	polyethylene	800	C96	96	50	OSR 50-5	16		33	50	Hydraulic	Manual	50	540	414	148	103	217
BETA HP 1000	polyethylene	1000	C96	96	50	OSR 50-5	16		33	50	Hydraulic	Manual	50	540	426	148	103	217