

MOUNTED FIELD SPRAYER AUTOMATIC "X" BOOM



- The spring system minimizing oscillation in rough terrain lift system that enables arm to be controlled from hydraulic control panel easily
- Long lasting and cleanable nozzle,
- Clean water tank independent from main tank there is control panel that provides homogeneous and precise spraying.
- float system that measures amount of water remaining in the tank precisely spraying pump with 4 membranes having the best performance
- Quick fill up
- The tank cleaning system that allows the tank to be washed after spraying.
- The chassis models are produced with high quality material by robotic welding.

Specification (unit)	Material of Tank	Capacity of Tank (Lt)	Pump Model (Piston Membrane)	Pump Flow (l/min)	Pump Pressure (Bar)	Control Panel	Work Width (m)	Nozzle Type	Number of Nozzles (number)	Distance Between Nozzles (cm)	Boom Height Adjustment	Boom's Folding Adjustment	Required Tractor Power (HP)	Operating Speed (r/min)	Weight (kg)	Length (cm)	Width (cm)	Height (cm)
DELTA D4	polyethylene	400	C 96	96	50	OSR 50-5	15	Conical brass nozzle	30	50	Hydraulic	Hydraulic	50	540	374	135	103	250
DELTA D6	polyethylene	600	C 96	96	50	OSR 50-5	15		30	50	Hydraulic	Hydraulic	50	540	394	135	103	250
DELTA D8	polyethylene	800	C 96	96	50	OSR 50-5	15		30	50	Hydraulic	Hydraulic	50	540	414	148	103	250
DELTA D10	polyethylene	1000	C 96	96	50	OSR 50-5	15		30	50	Hydraulic	Hydraulic	50	540	426	148	103	250