



• Pressure filter that increases spraying efficiency by filtering pressurized water clean water tank independent from main tank hose holder that ensures hoses to be organized between control and arm control that provides homogeneous and precise spraying norm

• Float system that measures amount of water remaining in the tank precisely filter system that can be cleaned easily and enables fast filling draining system that quickly drains the water remaining in the tank after spraying • Spraying pump with 4 membranes having the best performance tank washing system that allows the tank to be washed after spraying fiber

system that enables arm to be controlled from hydraulic control easily

• Durable and cleanable nozzle

• Reflector system that allows the machine to be noticed in traffic

• Pressure filter that increases spraying efficiency by filtering pressurized water

We reserve the right to make changes and / or improvements in designs & dimensions without notice and without incurring obligation.

Specification (unit)	Material of Tank	Capacity of Tank (Lt)	Pump Model (Piston Membrane)	Pump Flow ( I/min)	Pump Pressure (Bar)	Control Panel	Work Width (m)	Nozzle Type	Number of Nozzles (number)	Distance Between Nozzles (cm)	Boom Height Adjustment	Boom's Folding Adjustment	Required Tractor Power (HP)	Operating Speed (r/min)	Weight (kg)	Length (cm)	Width (cm)	Height (cm)	
ALFA UTP 1000	Polyethylene	1000	C145	145	50	OSR 50-5	15-18- 21-24	Conical Brass Nozzle	31	50	Hydraulic	Hydraulic	70-90	540	1000	225	190	310	