



MOUNTED FIELD SPRAYER HYDRAULIC BOOM

- Pressure filter that increases spraying efficiency by filtering pressurized water reflector system that allows the machine to be noticed in traffic .
- The lock system with pressure spring support the booms opening and closing stably.
- The spring system minimizing oscillation in rough terrain.
- Long lasting and cleanable nozzle,
- Clean water tank independent from main tank.
- The hose carrier to ensure the hoses tidy between the control panel and the boom there is control panel that provides homogeneous and precise spraying. Float system that measures amount of water remaining in the tank precisely.
- Easy cleanable and quick filling filter system draining system that quickly drains the water remaining in the tank after spraying spraying pump with 4 membranes having the best performance.
- The tank cleaning system that allows the tank to be washed after spraying.

Model		ALFA C 6	ALFA C 8	ALFA C 10
Material of Tank		Polythene	Polythene	Polythene
Capacity of Tank	Lt	600	800	1000
Pump Model		C96	C96	C96
Pump Flow	l/min	96	96	96
Pump Pressure	Bar	50	50	50
Control Panel		OSR 50-5	OSR 50-5	OSR 50-5
Work Width	m	16	16	16
Nozzle Type		Conical brass nozzle		
Number of Nozzles		33	33	33
Distance Between Nozzles	cm	50	50	50
Boom Height Adjustment		Hydraulic	Hydraulic	Hydraulic
Boom's Folding Adjustment		Manual	Manual	Manual
Required Tractor Power	HP	50	50	50
Operating Speed	r/min	540	540	540
Weight	kg	597	618	627
Length	cm	280	280	280
Width	cm	165	165	165
Height	cm	220	220	220

We reserve the right to make changes and or improvements in designs & dimensions without notice and without incurring obligation.