



MOUNTED ATOMIZER PULLEY BELT TYPE

- Fast filling
- Control that provides homogeneous and precise spraying norm
- Spraying pump with 4 membranes having the best performance
- Filter system with check valve that can be cleaned easily
- Modular chassis that is produced from high quality material with robotic welding
- Atomizer nozzle with adjustable spray angle and drop stopping feature
- Fan protection wire designed to prevent possible accidents
- Clean water tank independent from main tank
- Tank washing system that allows the tank to be washed after spraying
- Caps that provide direction during operation
- Separator system that allows the fan to be disengaged during operation

Model		DELTA E4	DELTA E6
Material Of Tank		Polyethylene	Polyethylene
Capacity of Tank	lt	400	600
Pump Model		C 96	C 96
Pump Flow	L/Min	96	96
Pump Pressure	Bar	50	50
Control Panel		OSR 50-3	OSR 50-3
Nozzle Type		Brass Stopper Turbo	Brass Stopper Turbo
Number of Nozzle	AD	10	10
Fan Diameter	cm	75	75
Working Widht	cm	12,16	12,16
Required Tractor Power	BG	50	50
Operating Speed	dev/dk	540	540
Air Flow Rate	m3/h	54000	54000
Weight	kg	225	235
Widht	cm	150	150
Length	cm	150	150
Height	cm	145	160

We reserve the right to make changes and or improvements in designs & dimensions without notice and without incurring obligation.