

- Fast filling
  Control that provides homogeneous and precise spraying norm
  Spraying pump with 4 membranes having the best performance
  Filter system with check valve that can be cleaned easily
- Modular chassis that is produced from high quality material with robotic welding
- Atomizer nozzle with adjustable spray angle and drop stopping feature
- Fan protection wire designed to prevent possible accidents
- Clean water tank independent from main tank
- Tank washing system that allows the tank to be washed after spraying
- Transmission that eliminates power loss and provides gradual transfer from pump to fan
- Caps that provide direction during operation

Model		DELTA F4	DELTA F6	DELTA F8	DELTA F10
Material Of Tank		Polyethylene	Polyethylene	Polyethylene	Polyethylene
Capacity of Tank	It	400	600	800	1000
Pump Model		C 96	C 96	C 96	C 96
Pump Flow	L/Min	96	96	96	96
Pump Pressure	Bar	50	50	50	50
Control Panel		OSR 50-3	OSR 50-3	OSR 50-3	OSR 50-3
Nozzle Type		Brass Stopper Turbo			
Number of Nozzle	pcs	10	10	10	10
Fan Diameter	cm	75	75	75	75
Working Width	cm	12,16	12,16	12,16	12,16
Required Tractor Power	BG	50	50	50	50
Operating Speed	r/min	540	540	540	540
Air Flow Rate	m3/h	54000	54000	54000	54000
Weight	kg	293	293	321	332
Width	cm	142	142	160	160
Length	cm	162	162	165	165
Height	cm	166	166	173	195